

FASTER, SMARTER, SAFER
SUMP CLEANER



The right tool to turn a dirty and difficult job into a fast, easy, and safe task.

SUMP SHARK SUMP CLEANER- SA5 AIR

The CECOR Sump Cleaner uses a high suction lift to remove metalworking fluid and sludge at 70 to 110 gallons per minute, filtering to separate metal working fluid from sludge. You can then discharge the filtered coolant at the same rate.

Save your company time and money by reducing machine tool downtime, labor costs, and mess.

- *Effectively and efficiently filter chips and sludge from industrial fluids for re-use (when applicable)*
- *Pump-in (suction) / Pump-out (discharge) capability*
- *Simple to operate and maintain with no moving parts.*
- *Proudly designed and manufactured in the U.S.A*



**HIGH POWERED
SUCTION**



**REDUCE LABOR
COST**



**KEEP FLUID
CLEAN**



**MULTIPOWER
OPTIONS**

www.cecorm.com

Specifications

Pump: Air Operated Venturi

Pumping Rate: Up to 70 gal/min (1 1/2" hose)
Up to 110 gal/min (2" hose)

Suction Lift: 26" Hg (mercury) or 350" water

Air Requirement: Air Headers- 3/4" or larger
Vertical Drops- 1/2" Hose or more
Line Pressure- 75 to 120 PSI
Volumetric Capacity- 53 to 80 CFM

Overfill Prevention: Automatic overfill protection
All discharge ports are valved

Pressure Discharge: 6 PSI with safety backup valve

Cleanout Door: 060-200 gal: 8" x 10" door w/ 1-1/4" drain port
300-600 gal: 16" dia hinged door with 2-1/2" drain port

Hose Options: 1 1/2" I.D x 16' or 2" I.D x 16'
Oil resistant PVC suction and discharge hose, including quick-disconnect coupler

Standard Tools: Flexible Nozzle
Flare Nozzle
Straight Nozzle

Additional Tools: Squeegee
Rake Tool Head
Hoe Tool Head
Extendable Tool Handle

Transport Options: Tow Bar Assembly
Fork Pockets
Custom Base (200 gallon+)

Filter Options

Filter Options: F10 Filter (1.0 cu ft capacity)
F23 Filter (2.3 cu ft capacity)

Filter Bag Options: Fine Cotton <500 micron
Poly =500 micron
Coarse Burlap >500 micron



F10 FILTER BASKET



F23 FILTER BASKET ASSEMBLY

CECOR Sump Cleaners come in a variety of gallon sizes:
(STANDARD UNITS BELOW)

PTL Base: 060, 090, 140, 200
TW Base: 300, 400, 500
Custom Base: 600