

The right tool to turn a dirty and difficult job into a fast, easy, and safe task.

## SUMP SHARK SUMP CLEANER-SD15 BATTERY

The CECOR Sump Cleaner uses a high suction lift to remove metalworking fluid and sludge at 60 to 110 gallons per minute, filtering to separate metal working fluid from sludge. You can then discharge the filtered

Save your company time and money by reducing machine tool downtime, labor costs, and mess.

coolant at the same rate.

- Effectively and efficiently filter chips and sludge from industrial fluids for re-use (when applicable)
- Pump-in (suction) / Pump-out (discharge) capability
- Simple to operate and maintain with no moving parts.
- Proudly designed and manufactured in the U.S.A









## www.cecor.com



## **Specifications**

Motor: Vacuum Motor

> Volts: 114 Amps: 14.2 Hertz: 60 Phase 1

**Battery:** Lithium 48VDC 20AH\*

\*SOLD SEPARATLY **Pumping** Up to 60 gal/min (1 1/2" hose)

Up to 100 gal/min (2" hose) Rate:

13" Hg (mercury) or 177" water **Suction Lift** 

Overfill Automatic overfill protection Prevention: All discharge ports are valved

Pressure 6 PSI with safety backup valve

Cleanout 060-200 gal: 8" x 10" door

w/1-1/4" drain port

300-600 gal: 16" dia hinged door with 2-1/2" drain port

Hose **Options:**  11/2" I.D x 16' or 2" I.D x 16' Oil resistant PVC suction and discharge hose, including quick-

disconnect coupler

Flexible Nozzle Standard Flare Nozzle Tools: Straight Nozzle

Squeegee Additional Rake Tool Head Hoe Tool Head Tools:

Extendable Tool Handle

Tow Bar Assembly **Transport** Fork Pockets **Options:** 

Custom Base (200 gallon+)

## Filter Options

**Filter Options:** 

F10 Filter (1.0 cu ft capacity) F23 Filter (2.3 cu ft capacity)

Filter Bag **Options:** 

Fine Cotton <500 micron Poly =500 micron

Coarse Burlap >500 micron

CECOR Sump Cleaners come in a variety of gallon sizes: (STANDARD UNITS BELOW)

PTL Base: 060, 090, 140, 200

TW Base: 300, 400, 500

Custom Base: 600



Discharge:

Door:

F10 FILTER BASKET



www.cecor.com