

FASTER, SMARTER, SAFER
SUMP CLEANER



The right tool to turn a dirty and difficult job into a fast, easy, and safe task.

SUMP SHARK SUMP CLEANER- SP50 PROPANE

The CECOR Sump Cleaner uses a high suction lift to remove metalworking fluid and sludge up to 110 gallons per minute, filtering to separate metal working fluid from sludge. You can then discharge the filtered coolant at the same rate.

Save your company time and money by reducing machine tool downtime, labor costs, and mess.

- *Effectively and efficiently filter chips and sludge from industrial fluids for re-use (when applicable)*
- *Pump-in (suction) / Pump-out (discharge) capability*
- *Simple to operate and maintain with no moving parts.*
- *Proudly designed and manufactured in the U.S.A*



**HIGH POWERED
SUCTION**



**REDUCE LABOR
COST**



**KEEP FLUID
CLEAN**



**MULTIPOWER
OPTIONS**

www.cec.or.com

Specifications

Engine: 20-HP Propane Engine

Pump: Lobe type, positive displacement air pump

Pumping Rate: Up to 110 gal/min

Suction Lift: 13" Hg (mercury) or 177" water

Overfill Prevention: Automatic overfill protection
All discharge ports are valved

Pressure Discharge: 6 PSI with safety backup valve

Cleanout Door: 16" dia hinged door with 2-1/2" drain port

Hose Options: 2" I.D x 16' oil resistant PVC suction hose
1 1/4" I.D x 16' discharge hose with full flow shut off nozzle

Standard Tools: Flexible Nozzle
Flare Nozzle
Straight Nozzle

Additional Tools: Squeegee
Rake Tool Head
Hoe Tool Head
Extendable Tool Handle

Transport Options: Tow Bar Assembly
Fork Pockets
Custom Base (200 gallon+)



F50 FILTER BASKET ASSEMBLY

Filter Options

Filter Options: F50 Filter (5.0 cu ft capacity)

Filter Bag Options: Fine Cotton <500 micron
Poly =500 micron
Coarse Burlap >500 micron

CECOR Sump Cleaners come in a variety of gallon sizes:
(STANDARD UNITS BELOW)

PTL Base: 200
TW Base: 300, 400, 500
Custom Base: 600